

GP7150A & GP7155A PUMP SPECIFICATIONS

Performance

	Power Required	Pressure	Max. Speed	Max. Flow	Max. Temp.	Plunger \varnothing	Plunger Stroke	Weight	NPSHR
Model	BHP (kW)	PSI (bar)	RPM	GPM (l/min)	°F (°C)	in (mm)	in (mm)	lbs. (kg)	ft. of head (mWs)
GP7150A	70.6 (52.7)	1900 (130)	700	54.4 (205.8)	140 (60)	1.97 (50)	1.89 (48)	375 (170)	26.2 (8.0)
GP7155A	65.7 (49.0)	1500 (100)	700	65.8 (249.1)	140 (60)	2.17 (55)	2.0 (52)	375 (170)	37.7 (11.5)

Figures given for maximum pressure and maximum speed (rpm) apply to intermittent operation with cold water.

When the pump is used in continuous operation and/or with water warmer than 104°F (40°C), these values must be reduced by 10%.

Performance data for intermittent operation, data for continuous operation on request.

For information on intermittent operation and calculating of the performance data, see the Giant Industries assembly instructions.

NPSHR / Inlet pressure

Required NPSH refers to water at 68 °F (20 °C) at maximum permissible pump speed.



Use of both suction connections is imperative in order to ensure cavitation-free operation and optimal suction conditions.

If only one connection is used, a safety margin of one meter has to be added to the required NPSH.

The inlet pressure on the suction side must not exceed 29 PSI (2 bar).

Level of noise emission

Emission sound pressure level: ≤ 91 dB(A)

Fields of application

The fields of application of these pump types correspond to the specifications in the assembly instructions Giant Industries, Inc.

Ambient conditions

Ambient temperature: $41^{\circ}\text{F} < T_{\text{Amb.}} < 86^{\circ}\text{F}$

Ambient temperature: $5^{\circ}\text{C} < T_{\text{Amb.}} < 30^{\circ}\text{C}$

Oil filling

- Filling quantity: **1.7 gallon (6.5 l)**
- Quality: Industrial gear oil ISO VG 220 or automotive gear oil **SAE 90 GL4 (Giant's p/n 01154)**
- Intervals: first oil change after **50 operating hours** then every 1000 operating hours, but at the latest after **12 months**

Installation/ Putting into Operation

Shaft protector

When the pump is in operation, the open shaft end must be covered up by shaft protector (21), the driven shaft side and coupling by a contact-protector and the plunger room by cover (30).

Direction of pump rotation

Set the direction of rotation of the drive unit according to the direction of rotation arrow on the crankcase.

Suction line filter

Recommended mesh size 150 μm .

Operation

For informations, see assembly instructions **Giant Industries, Inc.**

GP7150A Horsepower Requirements						
RPM	GPM	800 PSI	1000 PSI	1300 PSI	1500 PSI	1900 PSI
300	23.4	13.4	16.7	21.7	25.1	31.8
400	31.2	17.8	22.3	29.0	33.4	42.3
500	38.9	22.2	27.8	36.1	41.7	52.8
600	46.7	26.7	33.4	43.4	50.0	63.4
700	54.5	31.1	38.9	50.6	58.4	74.0

GP7155A Horsepower Requirements					
RPM	GPM	800 PSI	1000 PSI	1300 PSI	1500 PSI
479	45.0	25.7	32.1	41.8	48.2
531	49.9	28.5	35.6	46.3	53.5
585	55.0	31.4	39.3	51.1	58.9
638	60.0	34.3	42.9	55.7	64.3
700	65.8	37.6	47.0	61.1	70.5