

P200 SERIES



	Pump	LH/RH	DRIVE	SHAFT	BACKEND	UNLOADER	INJECTOR SIZE	THERMAL
Pump Model	P205	0.5 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM and 0.9 GPM @ 2000 PSI @ 3450 RPM						
	P206	0.8 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM and 1.5 GPM @ 2000 PSI @ 3450 RPM						
	P208	1.0 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM and 1.9 GPM @ 2000 PSI @ 3450 RPM						
	P230	1.1 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM and 2.0 GPM @ 2000 PSI (2500 PSI*) @ 3450 RPM						
	P209	1.5 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM and 2.7 GPM @ 2000 PSI @ 3450 RPM						
	P223	1.7 GPM @ 2000 PSI (3000 PSI*) @ 1750 RPM and 3.0 GPM @ 2000 PSI (3000 PSI*) @ 3450 RPM						
	P217	1.8 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM and 3.3 GPM @ 2000 PSI (2500 PSI*) @ 3450 RPM						
	P227	2.1 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM and 3.8 GPM @ 2000 PSI (2500 PSI*) @ 3450 RPM						
	P221	2.3 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM and 4.2 GPM @ 2000 PSI (2500 PSI*) @ 3450 RPM						
	P218	3.4 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM						
	P219	4.2 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM						
	P220	4.7 GPM @ 2000 PSI (2500 PSI*) @ 1750 RPM						
Shaft Side	LH Shaft	L						
	RH Shaft	R						
Electric Motor	(56C) 5 7/8" or 5.11" dia.	E1	(1) 01155 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07435)					
	(TC Face) 7 1/4" dia. Bolts	E2	(1) 06495 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07803)					
Gas Motor	(Under 9HP) 3-5/8" dia. Bolts	G1	(1) 01155 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07435 & (1) 09103)					
	(9HP & More) 6.5" dia. Bolts	G2	(1) 06478 / (4) 01176A-1 / (4) 01176-2 (Ass. Parts 06773, (4) 07804 & (4) 13129					
	(9HP & More) 6.5" dia. Bolts	B1	(1) 08499A					& (4) 13445 if needed
Coupler Size	5/8" Aluminum = 06505-0.6	B	(1) 06299 AND (1) 06332 with Each Aluminum Coupler ***** (1) 06332 with each plastic coupler					
	5/8" Delrin = 08494P	I						
	3/4" Aluminum = 06505-0.7	C						
	3/4" Delrin = 08496P	J						
	7/8" Aluminum = 06505-0.8	D						
	24mm Aluminum = 06505-24	M						
	1" Aluminum = 06505-1.0	E						
	1" Delrin = 08485P	K						
	1 1/8" Aluminum = 06505-1.1	F						
	1 1/8" Delrin = 08487P	L						
	1 3/8" Aluminum = 06505-1.3	H						
1 3/8" Delrin = 08489P	N							
Backend	Extended 08302-L(P200)					(4) 01196 / (4) 01176-2		
	Short Backend 08302(P200)	X				(4) 07188 / (4) 01176-2		
Unloader/Regulator	No Unloader/Regulator							
	Unloader/Regulator	23270 (P200)				U or R	For Regulators, add "R"	
	Unloader (Side of Shaft)	23270 (P200)				US or RS		
Siphon Injector	1.8mm (Fixed)					23750-1.8	2	
	2.1mm (Fixed)					23750-2.1	3	
	2.3mm (Fixed)					23750-2.3	4	
	1.8mm (Adjustable)					23750-1.8A	6	
	2.1mm (Adjustable)					23750-2.1A	7	
	2.3mm (Adjustable)					23750-2.3A	8	
Thermal	Thermal (Blank if No Thermal Relief Valve)					23422B (1/2")	T	

**Intermittent Duty Only*

NOTE: Pumps without Bell Housing to include (1) 01067 Associated parts

Method: Follow "shaded" boxes to follow the part number. Corresponding items included, next to the box.