

Rated Speed 375 RPM			Pressure at specific power inputs								Pump Head Style		
Type	FLOW		147 Hp	110 kW	177 Hp	132 kW	214 Hp	160 kW	268 Hp	200 kW	A	M	MC
	GPM	L/min	PSI	Bar	Hp	kW	Hp	kW	Hp	kW			
K 20018-3G	9.0	34	24650	1700	29580	2040	35815	2470	40600	2800	X		
K 20020-3G	11.1	42	19938	1375	23925	1650	29000	2000	36250	2500	X		
K 20022-3G	13.5	51	16240	1120	19575	1350	23635	1630	29000	2000	X		
K 20024-3G	16.1	61	13630	940	16313	1125	19720	1360	24650	1700	X		
K 20026-3G	19.0	72	11890	820	13993	965	16820	1160	20445	1410	X		
K 20028-3G	21.9	83	10440	720	12398	855	14718	1015	17618	1215	X		
K 20030-3G	25.1	95	9135	630	10948	755	13050	900	15370	1060	X		
K 20032-3G	28.8	109	8048	555	9570	660	11600	800	13485	930	X		
K 20036-3G	36.2	137	6308	435	7613	525	9208	635	10658	735	X		
K 20040-3G	44.9	170	5148	355	6090	420	7395	510	8628	595	X		
K 20045-3G	56.8	215	3915	270	4713	325	5655	390	6815	470	X	X	
K 20050-3G	70.0	265	3045	210	3698	255	4495	310	5510	380	X	X	
K 20055-3G	84.8	321	2538	175	3045	210	3698	255	4568	315		X	X
K 20060-3G	100.9	382	2175	150	2610	180	3118	215	3843	265		X	X
K 20065-3G	118.4	448	1813	125	2175	150	2683	185	3263	225		X	X
K 20070-3G	137.1	519	1595	110	1885	130	2320	160	2828	195			X
K 20075-3G	157.5	596	1378	95	1668	115	2030	140	2465	170			X
K 20085-3G	202.4	766	1088	75	1305	90	1523	105	1885	130			X
K 20095-3G	252.8	957	870	60	1088	75	1305	90	1523	105			X