

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P
1	Rated Speed 450 RPM			Pressure at specific power inputs								Pump Head Style				
2	Type	Flow		422 Hp	315 kW	476 Hp	355kW	536 Hp	400 kW	710 Hp	530 kW	A1	A2	M	MC1	MC2
3		GPM	L/min	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar					
4	K 50018-5G	18.2	69	35235	2430	39730	2740	44733	3085	50750	3500	X				
5	K 50020-5G	22.5	85	28493	1965	32190	2220	36250	2500	47053	3245	X				
6	K 50022-5G	27.2	103	23563	1625	26535	1830	29943	2065	38933	2685	X				
7	K 50024-5G	32.2	122	19793	1365	22330	1540	25158	1735	32698	2255	X				
8	K 50026-5G	37.8	143	16893	1165	18995	1310	21460	1480	27840	1920		X			
9	K 50028-5G	43.9	166	14573	1005	16385	1130	18488	1275	23998	1655		X			
10	K 50030-5G	50.5	191	12688	875	14283	985	16095	1110	20953	1445		X			
11	K 50032-5G	57.3	217	11093	765	12543	865	14138	975	18415	1270		X			
12	K 50036-5G	72.7	275	8773	605	9933	685	11165	770	14500	1000		X			
13	K 50040-5G	89.6	339	7105	490	8048	555	9063	625	11745	810		X			
14	K 50045-5G	113.3	429	5583	385	6308	435	7105	490	9280	640		X			
15	K 50050-5G	140	530	4568	315	5148	355	5800	400	7540	520		X	X		
16	K 50055-5G	169.4	641	3770	260	4205	290	4785	330	6235	430			X	X	
17	K 50060-5G	201.6	763	3118	215	3553	245	3988	275	5220	360			X	X	
18	K 50065-5G	236.5	895	2683	185	3045	210	3408	235	4423	305			X	X	
19	K 50070-5G	274.5	1039	2320	160	2610	180	2900	200	3843	265				X	
20	K 50075-5G	314.9	1192	2030	140	2248	155	2538	175	3335	230					X
21	K 50080-5G	358.3	1356	1740	120	1958	135	2248	155	2900	200					X
22	K 50085-5G	404.5	1531	1523	105	1740	120	1958	135	2610	180					X
23	K 50090-5G	453.6	1717	1378	95	1595	110	1740	120	2320	160					X
24	K 50095-5G	505.4	1913	1233	85	1450	100	1595	110	2103	145					X