





3.4 GPM @ 40,000 PSI* *other flows and pressures available

Ruggedly designed pump and diesel unit which features a compact design and continuous duty Kamat pump and over-sized engine. Available in a standard design or let us create a customized unit to meet your needs.

Applications:

- Surface Preparation
- Paint Removal
- Deburring

- Tank Cleaning
- · Hydrostatic Testing
- Heat Exchanger Cleaning

Standard Version:

- 135 HP Diesel engine, turbo charged with over-center clutch
- High pressure pump with spheroidal cast iron crankcase, drop-forged hardened, ground and polished crankshaft, bronze connecting rods and hardened stainless steel plungers
- 3/2 was on/off valve, pneumatically controlled
- Safety valve (rated for 46,000 PSI) which is adjustable and is capable of working multiple times
- Heavy duty trailer
- Water supply tank (30 gallons)
- Boost pump
- Diesel fuel supply of 55 gallons
- · Electronic controls for speed control of engine
- Gun/wand/nozzle/hose assembly
- 12 volt battery for electric start
- Stainless Steel Filter
- All necessary plumbing
- · Over-center clutch
- Belt-driven boos pump
- Manual

Optional Equipment:

- · Hydrostatic test unit including bleed-off control
- Automatic water fill valve
- · Low water shut down
- · Skid mounted versions
- Heavy duty filter with low inlet pressure alarm and connections

Sound reducing enclosure

