



Pipe Cleaning Nozzle - Aqua Twister 21,750 PSI (1500 bar)

rotating outer - ø 0.4" to 0.75" (ø 10 - 20 mm)

Drilled rotating nozzle made with hardened steel. It is designed with different jet angles for pipe cleaning in various industries.

For use with rigid lances or flexible hoses

Part No.	Outer ø in (mm)	Length in (mm)	Connection Female	Туре	Minmax. pipe inner ø in (mm)
7024243	0.39 (10)	1.81 (46)	M7	9010	0.59 - 1.18 (15 - 30)
7014072	0.47 (12)	1.89 (48)	1/8" BSP	9012	0.79 - 1.58 (20 - 40)
7024244	0.63 (16)	2.01 (51)	1/8" BSP	9016	0.98 - 2.36 (25 - 60)
7024245	0.71 (18)	2.22 (56.5)	1/4" BSP	9018	1.18 - 3.94 (30 - 100)
7025140	0.79 (20)	2.38 (60.5)	1/4" BSP	9020	1.38 - 4.72 (35 - 120)

Order example:

Part No. 7025140 - 5 Aqua Twister with 1/4" FBSP With jet angle no. 5 Type 9020-5

as well as indication of working pressure and flow rate of the used pump.



Jet angle No. Description		Jet angle
1	4 x90°	4 x 90
2	1x 0° 4x 90°	1 x 0
3	2 x 90° 2 x 45°	2 x 90 2 x 45
4	1 x 0° 2 x 90° 2 x 45°	2 x 90 1 x 0 2 x 45
5	2 x 10° 2 x 90° 2 x 45°	2 x 90 2 x 10 2 x 45
6	1 x 0° 2 x 10° 2 x 90° 2 x 45°	2 x 90 1 x 0 2 x 10 2 x 45

Jet angle No. Description		Jet angle
7	4 x 45°	4 x 45
8	1 x 0° 4 x 45°	1 x 0 4 x 45
9	2 x 10° 4 x 45°	2 x 10 4 x 45
10	1 x 0° 2 x 10° 4 x 45°	2 x 10 4 x 45
11	2 x 10° 4 x 75°	2 x 10 4 x 75
12	1 x 0° 2 x 10° 4 x 75°	1 x 0 4 x 75 2 x 10



WARNING: This product might contain a chemical known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov