

KOD 500-2500



Technical Data

Model*	Max. GPM (LPM)	Max. PSI (bar)	Outer Diameter in (mm)	Length in (mm)	Nozzles/ Rotor ø[mm]	Weight lbs. (kg)	Spray Angle	Connection Female
KOD 500	12.7 (48)	7,250 (500)	1.7" (43)	4.3" (109)	0.60-2.05	1.4 (0.65)	22°	1/4" BSP
KOD 800	10.0 (38)	11,600 (800)	1.7" (43)	5.2" (133)	0.60-2.05	1.5 (0.70)	22°	3/8" BSP
KOD 1000	9.2 (35)	14,500 (1000)	1.9" (49)	5.3" (135)	0.60-2.05	2.6 (1.2)	22°	3/8" BSP
KOD 1500	7.4 (28)	21,750 (1500)	1.9" (49)	5.3" (135)	0.60-2.05	2.6 (1.2)	22°	M14 x 1.5LH
KOD 2500	5.5 (21)	36,250 (2500)	1.9" (49)	5.3" (135)	0.60-1.55	2.9 (1.3)	22°	M26 x 1.5

*Maximum temperature 212 °F (100 °C)

When ordering please indicate model and nozzle size or flow and operating pressure

Applications

- Removal of concrete; laying bare reinforcements
- Cleaning and washing of concrete and stones

Note

When ordering nozzle inserts as replacements, always make sure that the drive tube with o-ring matches the actual rotor size fitted in the nozzle (see back).

That means: If it is intended to order a nozzle insert which differs in size from the rotor in the nozzle in original condition, it is essential in such cases to also order the corresponding drive tube with o-ring (see back page).