Standard Nozzles ≥ Pipe ø 1.6" (40 mm) for TORNADO Z71-3e

	Description	Part No.	Application
	Step nozzle short with fixed bores M 24x1.5 male - 39.6 GPM - 16,000 PSI (150 L/min - 1100 bar) M 24x1.5 male - 49.7 GPM - 16,000 PSI (188 L/min - 1100 bar)	7011080 7010745	General pipe cleaning for partially and fully blocked pipes of 1.6" (40 mm) inner diame-
	Step nozzle short with fixed bores and built-in pusher at 45° M 24x1.5 male - 39.6 GPM - 16,000 PSI (150 L/min - 1100 bar) M 24x1.5 male - 49.7 GPM - 16,000 PSI (188 L/min - 1100 bar)	7011081 7010385	ter and larger.
	Pusher with 2x ceramic inserts M4 M 24x1.5 male - 7.9 GPM - 16,000 PSI (30 L/min - 1100 bar) Ceramic insert M4 - diameter 0.8 mm	7010746	To be used in combination with all step nozzles short as driving nozzle "ALLCUT"
	Step nozzzle "ALLCUT" with fixed bores M 24x1.5 male - 39.6 GPM - 16,000 PSI (150 L/min - 1100 bar) M 24x1.5 male - 49.7 GPM - 16,000 PSI (188 L/min - 1100 bar) required accessories:	7011082	General pipe cleaning for partially and fully blocked pipes of 1.6" (40 mm) inner diame- ter and larger.
* *	Plug 1/4" BSP male or Front jetting insert 1/4" BSP male or Guide roller brass 1.26" dia. (32mm) and Axle 1/4" BSP male	5040036 7010903 7010748 7011192	Used to guide step nozzle "ALLCUT" Used to guide roller brass
	Nozzle carrier DT 2 - M 24x1.5 female for 2 nozzle inserts Form A + B Nozzle carrier DT 4 - M 24x1.5 female for 4 nozzle inserts Form A + B	7010388 7010389	General pipe cleaning for partially blocked pipes of 2.75" (70 mm) inner diameter and larger.
	<u>required accessories:</u> Nozzle holder for insert nozzle Insert nozzles O-Ring Screwdriver for nozzle holder	7010901 Z41-1 1060382 7010902	
**	<u>additional with:</u> Plug 1/4" BSP male or Front jetting insert 1/4" BSP male or Guide roller brass 1.26" dia. (32mm) and Axle 1/4" BSP male	5040036 7010903 7010747 7011083	Used to guide nozzle carrier DT Used to guide roller plastic