

HIGH-PRESSURE JETTING GUN KSP 500

Valve actuated

Z 1-1e

17.08.2022

Seite/Page 1/1

HP - Gun complete with spray tube
500 mm or 1000 mm and handle
without hose connector and nozzle)

KSP 500 with 500 mm spray tube
KSP 500 with 1000 mm spray tube

Part no. 7002580

Part no. 7002581



Hose connector G 1/2"
Hose connector M 22x1.5 DKL

Part no. 5040033

Part no. 1051093

Sleeve G 1/4" for screwed nozzles

Part no. 1050088



Technical Data

▪ max. working pressure	600 bar (60 MPa)
▪ max. capacity	80 l/min
▪ Connection	G ½ female
▪ Nozzle Connection:	G ¼ male
▪ Length total	650 mm or 1150 mm
▪ Weight	approx. 3 – 4 kg
▪ Temperature	max. 150° C
▪ Usable nozzle inserts	straight jet screwed nozzles type 0964

Applications

For manual surface cleaning of all types of forms and materials with nozzle.



For hand-held operation of a spray gun the nozzle diameter must be selected to ensure that the reaction force in the longitudinal axis when used at the max. operating pressure does not exceed 250 N. If the reaction force is in excess of 150 N the gun must be equipped with a support, in compliance with the European Norm EN 1829.

KAMAT GmbH & Co. KG

Salinger Feld 10, 58454 Witten, Germany,
Fon +49 (0) 23 02 / 89 03 - 0, Fax +49 (0) 23 02 / 80 19 17, info@KAMAT.de, www.KAMAT.de
Technische Änderungen vorbehalten / Technical data subject to change without notice

