

ORBITAL NOZZLES KOD 500 - 2500

For gun operations

Z 40-1e

17.08.2022

Seite/Page 1/1



Technical Data

Typ	max. °C	max. bar	Outer Ø mm	Length mm	Nozzles / Rotor Ø [mm]	Weight kg	α	Connection female
KOD 500 (F4)	100	500	43	109	0,60 – 2,05	0,65	22°	G 1/4" BSP
KOD 800 (F3)		800	43	132	0,60 – 2,05	0,7	22°	G 3/8" BSP
KOD 1000 (F2)		1000	49	135	0,60 – 2,05	1,2	22°	G 3/8" BSP
KOD 1500 (F1)		1500	49	135	0,60 – 2,05	1,2	22°	M14x1,5LH
KOD 2500 (F25) Black Edition		2500	49	149	0,60 – 1,55	1,3	22°	M26x1,5

When ordering please state model and nozzle size or flow and operating pressure.
Further nozzle sizes and adapters to fit all standard lance thread types are available on request

Applications

- Removal of concrete; laying bare reinforcements
- Cleaning and washing of concrete and stones

Note:

When ordering nozzle inserts as replacements always make sure that the drive tube with O-ring matches the actual rotor size fitted in the nozzle (see page Z40-4e). That means: If it is intended to order a nozzle insert which differs in size from the rotor in the nozzle in original condition, it is essential in such cases to also order the corresponding drive tube with O-ring (see page Z40-4e).

KAMAT GmbH & Co. KG

Salinger Feld 10, 58454 Witten, Germany,
Fon +49 (0) 23 02 / 89 03 - 0, Fax +49 (0) 23 02 / 80 19 17, info@KAMAT.de, www.KAMAT.de
Technische Änderungen vorbehalten / Technical data subject to change without notice

