

Drive Unit pneumatic 5/3500

Z65-2e

01.06.2018

Seite/Page 1/1

Technical Data

- Part No.: 7029561
- Max. working pressure: 3500 bar
- Max. flow rate: 50 l/min
- Connection inlet: M 26x1.5 female
- Connection shaft side: M 14x1.5 LH female
- **Important:** **No traverse loads permitted!**
- Width x Length: 102 mm x 223 mm
- Weight: approx. 2.5 kg
- Pneumatic Drive / Air motor
- Speed rpm: 0 - 1800 rpm
- Air requirement: 5,0 l/s
- Air working pressure: 6.3 bar
- Power: 120W



Note

Usable nozzle heads >>> see page P 35-1e with HP- Pipe nipple M 14x1.5 LH male >>> 7014047
See Rotating Nozzle PRD 3500 AIR >>> Page Z 30-1e

Technical Data

- Part No.: 7028990
- Max. working pressure: 3500 bar
- Max. flow rate: 50 l/min
- Connection inlet: M 26x1.5 female
- Connection outlet: Nozzle carrier Ø 80 mm (4x M 26x1.5 IG)
- **Important:** **No traverse loads permitted**
- Width x Length: 121 mm x 331 mm
- Weight: approx. 5,3 kg
- Pneumatic Drive / Air motor:
- Speed rpm: 0 - 1800 rpm
- Air requirement: 8,0 l/s
- Air working pressure: 6.3 bar
- Power: 300W

