

HPUD-65B Series



Fits in a Truck Bed

4.5 GPM @ 15,000 PSI *other common sizes on back

Ruggedly designed pump and diesel unit which features a compact design and continuous duty Giant pump and oversized engine. Available in a standard design or let us create a customized unit to meet your needs.

Other Common Versions:

- 6.0 GPM @ 12,000 PSI
- 7.0 GPM @ 10,000 PSI
- 15 GPM @ 4000 PSI
- 18 GPM @ 4000 PSI
- 22 GPM @ 3000 PSI

Applications:

- Surface Preparation
- Paint Removal
- Deburring
- Tank Cleaning
- Hydrostatic Testing
- Heat Exchanger Cleaning



Standard Version:

- 50 HP Kubota engine, turbo charged with over-center clutch
- High pressure pump with spheroidal cast iron crankcase, drop-forged hardened, ground and polished crankshaft, bronze connecting rods and hardened stainless steel plungers
- Flow (soft) unloader (rated to 15,000 PSI) which eliminates trapped pressure from discharge line
- Safety valve (rated for 17,400 PSI) which is adjustable and is capable of working multiple times
- Skid designed for standard pick up truck bed
- Boost pump
- Diesel fuel supply of 35 gallons
- Manual adjustment of engine speed
- Gun/wand/nozzle/hose assembly
- 12 volt battery for electric start
- Inlet "Y" strainer
- All necessary plumbing
- Manual

Optional Equipment:

- Electronic controls for speed control of engine
- Hydrostatic test unit including bleed-off control
- Automatic water fill valve
- Low water shut down
- Heavy duty filter with low inlet pressure alarm and connections
- Sound reducing enclosure