



Performance Under Pressure



Ultra-High Pressure Swivel Joint

for gun operation

Design & Advantages

- Swivel joint with triple bearings, stainless steel
- Rotating at maximum pressure
- Low pressure drop

Technical Data

| | |
|---------------------------|-----------------------|
| Part Number: | 7016705 |
| Maximum working pressure: | 23,200 PSI (1600 bar) |
| Maximum flow rate: | 18.5 GPM (70 L/min) |
| Gun connection: | M26 x 1.5 male |
| Hose connection: | M24 x 1.5 DKO |
| Diameter: | 1.54" (39 mm) |
| Total Length: | 5.0" (128 mm) |
| Weight: | 2.2 lbs. (1.0 kg) |



Additional equipment to connect hose lines

- 1x Adapter M 26 x 1.5 female - M 24 x 1.5 DKO

Part No. 7017120

Technical Data

| | |
|---------------------------|-----------------------|
| Part Number: | 7016960 |
| Maximum working pressure: | 43,500 PSI (3000 bar) |
| Maximum flow rate: | 10.6 GPM (40 L/min) |
| Gun connection: | M26 x 1.5 male |
| Hose connection: | M26 x 1.5 IG |
| Diameter: | 1.65" (42 mm) |
| Total Length: | 5.3" (135 mm) |
| Weight: | 2.2 lbs. (1.0 kg) |



Additional equipment to connect hose lines

- 1x Connector M 26 x 1.5 / M 14 x 1.5 LH

Part No. 7006361

Applications

- To be used with hand-operated spray guns
- To be used for connecting two hose lines



WARNING: This product might contain a chemical known to the State of California to cause cancer, and birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov